

Dynaudio 18S

Firmware update instructions

Skanderborg – September 2026

DYNAUDIO

Dynaudio A/S
Sverigesvej 15
DK-8660 Skanderborg
T: +45 8652 3411
dynaudio.com

Important note!

This firmware version (05.0010) merges all previous versions into one file, which includes all available presets. This version replaces all previous versions and includes all previous features and bugfixes.

Additional bugfixes in version 05.0010:

- Fixes an issue where absolute polarity was reversed. **Note:** After update, please re-check the Phase setting in the setup menu
- Fixes an issue where PEQ settings in some cases were deactivated after standby

Requirements

- Empty USB stick, formatted to FAT32. Max size is 8 GB.
- The latest firmware file downloaded from 18S section on www.dynaudio.com

Presets

This version includes presets for the following products:

• BM6 Classic
• BM15 Classic
• BM5 mkIII
• LYD 5
• LYD 7
• LYD 8
• LYD 48

(See next page for instructions)



DYNAUDIO

Dynaudio A/S
Sverigesvej 15
DK-8660 Skanderborg
T: +45 8652 3411
dynaudio.com

Steps

1. Unzip the downloaded Zip file.
2. Copy the '*DYNAUDIO.bin*' firmware file into the root directory of the USB stick.
3. Switch OFF the subwoofer with the rear-panel switch.
4. Insert the USB stick into the USB port at the rear panel labeled 'Service'.
5. Switch ON the subwoofer with the rear-panel switch.
6. Your subwoofer will automatically download the firmware from the USB stick.
7. After this, let the sub install the full update, which should take 1-3 minutes. **DON'T TURN IT OFF**.
8. During this update the LED will change from red to blue, and display various messages about the update progress.
9. After installation is complete, the LED will turn green and the display will return the message: *Update result: Success!*
10. Your firmware update procedure is now finished. Switch OFF the subwoofer, and remove the USB stick.
11. Switch ON the subwoofer.
12. Check the firmware version in the menu info screen.